

## **ASTM E84 FIRE RATING STATEMENT**

Oct, 2025

Arlon Graphics declare that the graphic films we supply have been tested for Surface Burning Characteristics of Building Materials in accordance with the procedure outlined in ASTM E 84 (ANSI/UL 723; NFPA 225; and UBC 8-1).

This applies to the following products:

Product Name	Rating	Flame Spread	Smoke Developed
Digital Print Film (DPF)			
SLX+	А	0	35
Omni Cast Wrap	Α	0	50
DPF 6000XRP	А	10	0
DPF 6000RP White	Α	5	30
DPF 6100XLP	А	0	10
DPF V9700	А	15	0
DPF V9500	А	15	0
DPF 4600GLX	Α	0	15
DPF 8000 Ultra Tack	А	0	0
DPF 8200 High Tack	Α	5	100
DPF 8200X High Tack	А	15	20
DPF 4200 Matte	Α	15	10
DPF 4200 Canvas	А	20	25
DPF 4300	Α	0	5
DPF 4400	А	0	200
DPF 5200 007 Silver	Α	5	45
DPF 5200 314 Frosted	А	0	50
DPF 4500GX	Α	20	20
DPF 4550GT	А	15	35
DPF 4550GTX	Α	15	60
DPF 510GTR+Series 3510	А	20	115
Overlaminate Series			
Series V3370G	Α	15	0
Series V3370S	А	15	0
Series 3210G	Α	10	40
Series 3170M	А	15	0
Series 3220G	А	5	0
Series 3270G	А	5	105
Series 3420G	Α	20	75
Series 3450G	А	15	200
Series 3510G	Α	20	115
Series 3350	А	10	5

P +86 0536 6226568



Arlon declares that no formula changes which have impact on tested properties have been made to any of the mentioned products during the period between testing and present. There is also no distinction between colors of tested film.

Prepared by:

Chi Chan

Tech Service Engineer Arlon Graphics, LLC.

hi Chan

