



AS 5637.1-2015 FIRE RATING STATEMENT

Nov 2025

ARLON

Arlon Graphics declare that the graphic films we supply have been tested for Surface Burning Characteristics of Building Materials in accordance with the procedure outlined in AS/NZS 3837-1998 Method.

This applies to the following products:

Product Name	NCC Group Number	Smoke Growth Rate (sqm/kg)
Digital Print Film (DPF)		
DPF V9500	1	8.3
Omni Cast Wrap	1	19.3
DPF 4150 HT	1	57
DPF 4150 MR	1	31.9
DPF 4200 Matte	1	68.2
DPF 4200 Canvas	1	32.5
DPF 4550 GTX-HT	1	33.6
DPF 4580GX-OH	1	48.3
DPF 4600GLX	1	46.1
DPF 4650GLX	1	26.0
DPF 8200 High Tack	1	52.2
DPF 510GTRX + Series 3510	1	54.3
DPF 510GTX-HT + Series 3510	1	56.3
DPF 510GTX-HT	1	8.7
Overlamine Series		
Series V3370	1	17.6
Series 3460G	1	27.9
Series 3460M	1	32.3
Series 3420G	1	49
Series 3420M	1	42.5
Cut Graphics Series		
Series 5800X	1	1.9

Arlon declares that no formula changes which have impact on tested properties have been made to any of the mentioned products during the period between testing and present. There is also no distinction between colors of tested film.

Prepared by:

Chi Chan

Chi Chan
Tech Service Engineer
Arlon Graphics, LLC.



1

USA

a 200 Boysenberry Lane, Placentia, CA 92870
p 800 232 7161 / +1 714 985 6300
f +1 714 985 6305

EUROPE

a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
p +31 70 354 4311
f +31 70 355 7721

CHINA

a No. 1989 Xinchang Road, Weifang, Shandong, 262400
p +86 0536 6226568

arlon.com