



## ▶ DPF 206

### Removable Interior Woven Wall Decoration Film

DPF 206 is a 6-mil (150 micron) light weight polycoated matte white film with a unique woven texture. The clear removable pressure-sensitive adhesive is designed to bond well to substrates such as smooth painted non-vinyl walls. DPF 206 has a lay-flat liner that is optimal for printing on a variety of print systems. This is the ideal film for wall decorations that require ease of application as well as removability.

### APPLICATIONS & FEATURES

- Interior Wall decorations, advertising and murals on smooth painted non-vinyl walls.
- Digital printing with a wide variety of direct print systems, such as solvent, UV and UV screen.

### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
<b>SURFACE FINISH</b>	Gloss Meter 60° Reflection	≤ 10 units	
<b>THICKNESS</b>	Micrometer, Federal Bench Type	6-mil (150 micron)	
<b>TENSILE STRENGTH</b>	Tensile Tester 2-in (51 mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s)	100 lb/in	18 kg/cm
<b>ELONGATION</b>	Instron Tensile Tester as above	≥ 30%	
<b>SHELF LIFE</b>	Free from excessive moisture, temperature, direct sunlight	2 Years	
<b>STORAGE TEMPERATURE</b>	85°F or lower		
<b>APPLICATION TEMPERATURE RANGE</b>	On clean, dry substrate	50°F to 90°F	10°C to 30°C
<b>SERVICE TEMPERATURE RANGE</b>	On clean, dry substrate	-40°F to 176°F	-40°C to 80°C
<b>DIMENSIONAL STABILITY</b>	Shrinkage After 158°F (70°C), 48 hours aging	< 25-mils	< 0.635 mm
<b>PEEL ADHESION</b>	PSTC-1, 15 min, RT 70°F (21°C)	0.31 lb/in	0.05 kg/cm
<b>LINER RELEASE</b>	TLMI Release at 90°, 300 in/min (760 cm/min)	160 g/2 in	30 g/cm

Standard Terms & Conditions Apply

## TERMS & CONDITIONS

*The following is made in lieu of all warranties expressed or implied:*

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

## ADDITIONAL CONSIDERATIONS

Arlon does not guarantee the successful application or removal of this film to painted interior & exterior walls due to the wide varieties in paints and sealants, especially for zero or low VOC paints.

If used for applications besides those recommended in this Product Information Bulletin, it is highly recommended that the customer determine the compatibility and removability of the product and paint in question. Your Arlon Sales Manager can provide a Wall Wrap Questionnaire to help understand product performance requirements.

September 2016

USA:  200 Boysenberry Lane, Placentia, CA 92870, USA  
EUROPE:  North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands  
UK:  P6 Parklands, Heywood Distribution Park, Heywood, Lancashire OL102TT, UK

 800 232 7161/+1 714 985 6300  800 329 2756  
 +31 70 354 4311  +31 70 355 7721  
 +44 161 884 0592  +31 70 355 7721

arlon.com