



ARLON

# DPF 4150M-HT

DPF 4150M-HT can be used for a wide range of interior applications such as wall décor, advertising and murals on smooth painted walls, retail POP displays, home and office décor. The adhesive is specially designed to adhere to substrates such as smooth to slightly textured painted walls as well as low or no VOC paints. The thickness of the film enables ease of application without the need for an overlaminate. DPF 4150M-HT has a premium moisture stable poly-coated lay-flat liner that is optimal for printing on a variety of print systems.

## Unique Features:

- ▶ Registration of panels made easy due to rigidity of film
- ▶ Compatible with most paint types, including a wide range of zero and low-VOC paint types
- ▶ Fire certified for Australian Fire Standard AS 5637

## Applications:

- ▶ Interior wall décor
- ▶ POP displays
- ▶ Smooth Painted Interior Walls

## Performance & Physical Data

Finish:	Matte
Durability (Unprinted):	5 Years
Roll Widths:	1.37m / 1.52m / 1.6m
Roll Lengths:	50 m
Adhesive:	Permanent (Clear)
Release Liner:	Lay-Flat Polycoated
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlaminate:	Series 3450



## USA

- a 200 Boysenberry Lane, Placentia, CA 92870
- p 800 232 7161 / +1 714 985 6300
- f +1 714 985 6305

## EUROPE

- a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p +31 70 354 4311
- f +31 70 355 7721

## CHINA

- a No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p +86 0536 6226568

arlon.com

June 2025