



**ARLON**

# DPF 4150MR

DPF 4150MR features a high quality polymeric facestock ensuring exceptional graphics for intermediate graphics and removable adhesive removeable up to 1 year with the aid of heat and chemicals. The adhesive is specially designed to adhere to substrates such as smooth to slightly textured painted walls as well as low or no VOC paints. The thickness of the film enables ease of application without the need for an overlamine. DPF 4150MR has a premium moisture stable poly-coated lay-flat liner that is optimal for printing on a variety of print systems.

## Unique Features:

- ▶ Registration of panels made easy due to rigidity of film
- ▶ Compatible with most paint types, including a wide range of zero and low-VOC paint types
- ▶ Removable up to 1 year with the aid of heat and chemical
- ▶ Fire certified for Australian Fire Standard AS 5637

## Applications:

- ▶ Interior wall décor
- ▶ POP displays
- ▶ Smooth Painted Interior Walls

## Performance & Physical Data

<b>Finish:</b>	Matte
<b>Durability (Unprinted):</b>	5 Years
<b>Roll Widths:</b>	1.37m / 1.52m / 1.6m
<b>Roll Lengths:</b>	50 m
<b>Adhesive:</b>	Removable (Clear)
<b>Release Liner:</b>	Lay-Flat Polycoated
<b>Ink Compatibility:</b>	Eco-Solvent Solvent UV Latex
<b>Compatible Overlamine:</b>	Series 3450



## USA

- a** 200 Boysenberry Lane, Placentia, CA 92870
- p** 800 232 7161 / +1 714 985 6300
- f** +1 714 985 6305

## EUROPE

- a** Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p** +31 70 354 4311
- f** +31 70 355 7721

## CHINA

- a** No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p** +86 0536 6226568

[arlon.com](http://arlon.com)

June 2025