



► DPF 4150MR Vinyl Film

Removable Interior Wall Decoration Vinyl Film

DPF 4150MR is a 6-mil (150 micron) white vinyl film with a clear, removable, pressure-sensitive adhesive intended for interior wall applications, available in Matte finish. The adhesive is specially designed to adhere to substrates such as smooth to slightly textured painted walls as well as low or no VOC paints. The thickness of the film enables ease of application without the need for an overlamine. DPF 4150MR has a premium moisture stable poly-coated lay-flat liner that is optimal for printing on a variety of print systems. The high quality polymeric facestock ensures exceptional graphics for intermediate graphics. DPF 4150MR is rated for indoor durability up to 5 years (unprinted).

APPLICATIONS & FEATURES

- Interior wall décor, advertising and murals on smooth painted walls, retail POP displays, home and office décor
- Registration of panels made easy due to rigidity of film
- Compatible with most paint types, including a wide range of zero and low-VOC paint types
- Removable up to 1 year with the aid of heat and chemical
- Superior print quality with a wide variety of print systems: Eco-Solvent, Solvent, Latex, and UV
- Fire certified for Australian Fire Standard AS 5637
- Refer to Arlon's recommended installation bulletin for walls preparation, application and removal. Please note that Arlon does not warrant damage to the interior wall surface upon removal even if removable adhesive is used.

PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
SURFACE FINISH	Gloss Meter 60° Reflection	≤ 20 Gloss Units	
THICKNESS	Micrometer, Federal Bench Type	6-mil (150 microns)	
TENSILE STRENGTH	ASTM D882	≥ 2.7 kg/cm	≥ 15 lb/in
ELONGATION	Instron Tensile Tester as above	≥ 150%	
SHELF LIFE (IN BOX)	Ideal Storage Temperature 70°F (21°C) and 50% relative humidity	1 year from factory shipment	
APPLICATION TEMPERATURE RANGE	On clean, dry substrate	50°F to 85°F	10°C to 30°C
SERVICE TEMPERATURE RANGE	On clean, dry substrate	-20°F to 150°F	-29°C to 65° C
DIMENSIONAL STABILITY	158°F (70°C), 48 hours aging	< 25 mil	< 0.635 mm
PEEL ADHESION	FTM 1, 15 min, RT 72°F (23°C)	> 0.09 kg/cm	> 0.5 lb/in
LINER RELEASE	FTM 3	5-20 g/in	

Standard Terms & Conditions Apply

USA

- a** 200 Boysenberry Lane
Placentia, CA 92870
- p** 800 232 7161 / +1 714 985 6300
- f** +1 714 985 6305

EUROPE

- a** Dr. Lelykade 22B, 2583CM
Den Haag, The Netherlands
- p** +31 70 354 4311
- f** +31 70 355 7721

AUSTRALIA

- a** 18 Axis Crescent
Dandenong South, VIC 3175
- p** +61 3 8751 7999

CHINA

- a** No. 1989 Xinchang Road
Weifang, Shandong, 262400
- p** +86 0536 6226568

PREPARATION & INSTALLATION

Interior walls can be challenging when working with a wide variety of paint systems, such as zero or low VOC paints, and when combined with various preparation techniques. For this reason, we have put together a comprehensive installation guide containing our recommended installation techniques to achieve a successful installation with our wall films. The installation guide can be found by visiting arlon.com.

ADDITIONAL CONSIDERATIONS




Arlon does not guarantee the successful application or removal of this film to painted interior & exterior walls due to the wide varieties in paints and sealants. If used for applications besides those recommended in this Product Information Bulletin, it is highly recommended that the customer determine the compatibility and removability of the product and paint in question. Your Arlon Sales Manager can provide a Wall Wrap Questionnaire to help understand product performance requirements.




TERMS AND CONDITIONS

The warranties offered in Arlon's Standard Terms and Conditions, which are incorporated in full by this reference and are available at https://www.arlon.com/na_en/legal/terms-and-conditions, are made in lieu of all other express or implied warranties."




June 2025

USA



-  200 Boysenberry Lane
Placentia, CA 92870
-  800 232 7161 / +1 714 985 6300
-  +1 714 985 6305

-  6110 Rittiman Road
San Antonio, TX 78218
-  800 549 9860 / +1 210 798 1900
-  +1 210 798 1939


EUROPE

-  Dr. Lelykade 22B, 2583CM
Den Haag, The Netherlands
-  +31 70 354 4311
-  +31 70 355 7721

AUSTRALIA

-  18 Axis Crescent
Dandenong South, VIC 3175
-  +61 3 8751 7999

CHINA

-  No. 1989 Xinchang Road
Weifang, Shandong, 262400
-  +86 0536 6226568