



## ► DPF 4500GLX/MLX

### Intermediate Calendered Digital Print Pressure-Sensitive Vinyl Film with X-Scape Technology®

DPF 4500GLX/MLX is constructed of a 3-mil (75 micron) white calendered film offered in gloss or matte and coated with tinted, bubble releasing, permanent pressure-sensitive adhesive. The LX (Low Profile) X-Scape System allows installers to achieve speedy installation while maintaining high enough tack to ensure long-term bond. The polymeric facestock allows for vibrant prints combined with ease of application for short and medium-term graphics.

DPF 4500GLX/MLX is rated for outdoor durability up to 5 years (unprinted). Printed durability is dependent on the ink system used.

### APPLICATIONS & FEATURES

- Digital printing with a wide variety of direct print systems
- Short to medium-term signage, POP displays, flat surfaces, kiosks and tradeshow\*
- Compatible with Series 3220, Series 3170, and Series 3420 overlaminates

### PERFORMANCE & PHYSICAL DATA

PROPERTY	TEST METHODS	TYPICAL VALUE	
SURFACE FINISH	Gloss Meter 60° Reflection	80 to 90 Gloss Units (Gloss) 10 to 15 Gloss Units (Matte)	
THICKNESS	Micrometer, Federal Bench Type	3-mil (75 micron)	
TENSILE STRENGTH	Tensile Tester 2-in (51mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s)	13 lb/in	2.3 kg/cm
ELONGATION	Instron Tensile Tester as above	≥ 170%	
SHELF LIFE (IN BOX)	Ideal Storage Temperature 70°F (21°C) and 50% relative humidity	1 year from factory shipment	
APPLICATION TEMPERATURE RANGE	On clean, dry substrate	50°F to 90°F	10°C to 32°C
SERVICE TEMPERATURE RANGE	On clean, dry substrate	-20°F to 150°F	-29°C to 65°C
DIMENSIONAL STABILITY	Shrinkage After 158°F (70°C), 48 hours aging	0.025 in	0.64 mm
PEEL ADHESION	PSTC-1, 15 min, 70°F (21°C)	2.5 lb/in	0.45 kg/cm
LINER RELEASE	TLMI Release at 90°, 300 in/min (760 cm/min)	60 g/2 in	11.81 g/cm

\*Recommended to test compatibility on raw & primed MDO prior to installation due to variation in substrate properties




Standard Terms & Conditions Apply

### TERMS & CONDITIONS




The warranties offered in Arlon's Standard Terms and Conditions, which are incorporated in full by this reference and are available at [https://www.arlon.com/na\\_en/legal/terms-and-conditions](https://www.arlon.com/na_en/legal/terms-and-conditions), are made in lieu of all other express or implied warranties.

July 2025



#### USA

-  200 Boysenberry Lane, Placentia, CA 92870
-  800 232 7161 / +1 714 985 6300
-  +1 714 985 6305

#### EUROPE

-  Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
-  +31 70 354 4311
-  +31 70 355 7721

#### CHINA

-  No. 1989 Xinchang Road, Weifang, Shandong, 262400
-  +86 0536 6226568