



ARLON

DPF 510GTRX

DPF 510GTRX is a 3.2-mil (80 micron) calendered film with a tinted, removable pressure-sensitive adhesive and a low profile air-egress, lay-flat liner. With X-Scape Technology®, it ensures a bubble-free installation and a smooth, paint-like finish, making it ideal for promotional graphics and beyond. This film provides uniform ink receptivity across most printing systems, resulting in vibrant, high-quality graphics. Its light gray, clean removing adhesive facilitates easy application while providing sufficient opacity to cover existing graphics. For enhanced abrasion resistance, pair DPF 510GTRX with Series 3510 overlamine. DPF510GTRX is rated for outdoor durability up to 3 years (unprinted). Printed durability is dependent on the ink system used.

Unique Features:

- ▶ Low Profile X-Scape Technology® for Easy, Bubble-Free Installations
- ▶ Cleaning Removing Adhesive
- ▶ Consistent Performance with High Heat Printers
- ▶ Certified to ASTM E 84 Class A

Applications:

- ▶ Short-Term Interior or Exterior Signage
- ▶ POP / Trade Show Graphics
- ▶ Decals



Performance & Physical Data

Finish:	Gloss
Durability (Unprinted):	3 Years
Roll Widths:	50" (1.37 m) 60" (1.6 m)
Roll Lengths:	50 yards (45.72 m)
Adhesive:	Removeable (Tinted)
Release Liner:	Lay-Flat Polycoated with Low Profile X-Scape Technology®
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlamine:	Series 3510

USA

- a 200 Boysenberry Lane, Placentia, CA 92870
- p 800 232 7161 / +1 714 985 6300
- f +1 714 985 6305

EUROPE

- a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p +31 70 354 4311
- f +31 70 355 7721

CHINA

- a No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p +86 0536 6226568

arlon.com

July 2025