



ARLON

DPF 510GTR / MTR

DPF 510 delivers a consistent, vibrant print quality at an unbeatable value for your short-term applications. The two sided, lay-flat polycoated liner ensures that the vinyl will not curl under heavy heat from printers, is resistant to high humidity and makes your graphic easier to handle and install. DPF 510 has consistent ink receptivity across most print systems. The low tack removable solvent-based adhesive allows for easy removal of up to one year and can be used with dry or wet applications. Combine DPF 510 with Series 3510 overlaminates for an easier installation and abrasion resistance.

Only available in the Americas and Australia/New Zealand.

Unique Features:

- ▶ Exceptional, Vibrant Print
- ▶ Consistent Performance with High Heat Printers
- ▶ High-Quality Clean Removing Adhesive

Applications:

- ▶ Short-Term Interior or Exterior Signage
- ▶ Windows
- ▶ POP / Trade Show Graphics
- ▶ Decals



Performance & Physical Data

Finish:	Gloss / Matte
Durability (Unprinted):	3 Years
Roll Widths*:	54" (1,37 m), 60" (1,52 m)
Roll Lengths:	50 Yards (45,72 m)
Adhesive:	Low Tack Removable (Tinted)
Release Liner:	Lay-Flat Polycoated
Ink Compatibility:	Eco-Solvent Solvent Latex
Compatible Overlaminates:	Series 3510

*Sizes can be custom ordered

USA: 200 Boysenberry Lane, Placentia, CA 92870, USA
 EUROPE: North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands

800 232 7161 / 714 985 6300 800 329 2756
 +31 0 70 354 4311 +31 0 70 355 7721

arlon.com

July 2018