



ARLON

# DPF 510GTR / MTR

DPF 510 delivers a consistent, vibrant print quality at an unbeatable value for your short-term applications. The two sided, lay-flat polycoated liner ensures that the vinyl will not curl under heavy heat from printers, is resistant to high humidity and makes your graphic easier to handle and install. DPF 510 has consistent ink receptivity across most print systems. The low tack removable solvent-based adhesive allows for easy removal of up to one year and can be used with dry or wet applications. Combine DPF 510 with Series 3510 overlamine for an easier installation and abrasion resistance.

## Unique Features:

- ▶ Exceptional, Vibrant Print
- ▶ Consistent Performance with High Heat Printers
- ▶ High-Quality Clean Removing Adhesive

## Applications:

- ▶ Short-Term Interior or Exterior Signage
- ▶ Windows
- ▶ Decals
- ▶ Interior Floor Graphics

## Performance & Physical Data

|                         |                              |
|-------------------------|------------------------------|
| Finish:                 | Gloss / Matte                |
| Durability (Unprinted): | 3 Years                      |
| Roll Widths*:           | 54" (1,37 m), 60" (1,52 m)   |
| Roll Lengths:           | 50 Yards (45,72 m)           |
| Adhesive:               | Low Tack Removable (Tinted)  |
| Release Liner:          | Lay-Flat Polycoated          |
| Ink Compatibility:      | Eco-Solvent Solvent UV Latex |
| Compatible Overlamine:  | Series 3510                  |

\*Sizes can be custom ordered



Certified for  
HP Latex Inks

## USA

- a 200 Boysenberry Lane, Placentia, CA 92870
- p 800 232 7161 / +1 714 985 6300
- f +1 714 985 6305

## EUROPE

- a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p +31 70 354 4311
- f +31 70 355 7721

## CHINA

- a No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p +86 0536 6226568

arlon.com

June 2025