



## ► DPF 6700

### Cast Wall Wrap Film

DPF 6700 is a 2-mil (50 micron) cast highly conformable film with aggressive permanent adhesive. The film is specially formulated to conform to “hard-to-stick”, highly textured masonry surfaces such as brick, stucco, and concrete. When printed, DPF 6700 has a warranty of 1 year on masonry surfaces\*.

### APPLICATIONS & FEATURES

- Digital printing on a wide variety of direct print systems.
- Highly textured surfaces such as, brick, stucco, concrete, etc.
- Wall murals.
- Used in conjunction with Series 3200, Series 3210, Series 3220, Series 3310, or Series 3170 overlaminates.

### PERFORMANCE & PHYSICAL DATA

Certified for  
HP Latex Inks

PROPERTY	TEST METHODS	TYPICAL VALUE	
SURFACE FINISH	Gloss Meter 60° Reflection	70 to 90 Gloss Units	
THICKNESS	Micrometer, Federal Bench Type	2-mil (50 micron)	
TENSILE STRENGTH	Tensile Tester with 2-in (51 mm) jaw separation; crosshead speed of 12 in/min. (5.1 mm/s), web direction	≥ 4.5 lb/in width	≥ 1.25 kg/cm width
ELONGATION	Instron Tensile Tester as above	≥ 150%	
SHELF LIFE	Free from excessive moisture, temperature, direct sunlight	2 Year from factory shipment	
APPLICATION TEMPERATURE RANGE	On clean, dry substrate	50°F to 100°F	4°C to 38°C
SERVICE TEMPERATURE RANGE	On clean, dry substrate	-40°F to 175°F	-20°C to 70°C
DIMENSIONAL STABILITY	Shrinkage after 158°F (70°C), 48 hours aging	0.010 in	0.25 mm
PEEL ADHESION	PSTC-1, 15 min, RT 70°F (21°C)	≥ 4.0 lbs/in	≥ 0.71 kg/cm
LINER RELEASE	TLMI Release at 90°, 300 in/min (760 cm/min)	40 g/2 in	8 g/cm

\*6 month warranty for freeze and thaw zones, Arlon custom warranty must be requested for all DPF 6700 applications on masonry surfaces.

Please contact your Regional Sales Manager for details.

\*Standard Terms & Conditions Apply

#### USA

**a** 200 Boysenberry Lane, Placentia, CA 92870  
**p** 800 232 7161 / +1 714 985 6300  
**f** +1 714 985 6305

#### EUROPE

**a** Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands  
**p** +31 70 354 4311  
**f** +31 70 355 7721

#### CHINA

**a** No. 1989 Xinchang Road, Weifang, Shandong, 262400  
**p** +86 0536 6226568

## PREPARATION & INSTALLATION

### Masonry Surfaces (Brick, Cinder Block and Concrete)

The surface should be entirely dust free: high pressure TSP/water wash is the easiest method. Please ensure there must be no loose paint, grit or chalk present. All surfaces must be completely dry prior to applying vinyl.

The surface temperature must be above 50°F. To assure highest adhesion the graphics will benefit from a final installation pass using a soft roller and heat source in combination. The film should be heated to a point of softening and then roll the film tightly into the texture of the wall.

## REMOVAL

Addition of heat during removal will make the process much cleaner and faster. Where possible allow the surface to reach 80°F/27°C or more before removing the film. Where ambient temperature is not that high use either a very “soft” flame type torch or heat gun to bring the temperature up. Arlon recommends getting the film and under laying adhesive above 100°F/38°C.

Remove the film in a continuous smooth motion at a shallow angle for the fastest separation. Where it is practical, two people on the removal make the job go far faster than using just one. With one person working the heating unit in front of the second person who is peeling film, the job proceeds at a uniform and consistent pace. Where only one person is working there will be constant starting and stopping in addition to the problems of the heat being very inconsistent.

## SPECIAL CONSIDERATIONS

Because of the porous nature of all masonry and its general roughness Arlon does expect water, snow or ice to seep between the film and wall and collect on the upper edges of the applied graphic. For this reason applications to very rough surfaces do not carry the standard warranties. Those regions where extreme temperatures are experienced (freeze/thaw cycles); The warranty is reduced by 50%.




Standard warranty applies to vertical applications only. Vertical is defined as +/- 10° from the vertical. Non-vertical applications are not warranted for this product.

## TERMS & CONDITIONS




The warranties offered in Arlon's Standard Terms and Conditions, which are incorporated in full by this reference and are available at [https://www.arlon.com/na\\_en/legal/terms-and-conditions](https://www.arlon.com/na_en/legal/terms-and-conditions), are made in lieu of all other express or implied warranties.”

June 2025



#### USA

 200 Boysenberry Lane, Placentia, CA 92870  
 800 232 7161 / +1 714 985 6300  
 +1 714 985 6305

#### EUROPE

 Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands  
 +31 70 354 4311  
 +31 70 355 7721

#### CHINA

 No. 1989 Xinchang Road, Weifang, Shandong, 262400  
 +86 0536 6226568