

DPF 8200 HIGH TACK

DPF 8200 High Tack is the ultimate premium film for textured surfaces and installations on demanding surfaces. A durable film combined with a low shrink, high tack adhesive formula that allows for greater dimensional stability - making it easier to apply. With reduced converting and printing time, you can remain focused producing brilliant graphics. Adding heat to the DPF 8200 High Tack when installing on textured surfaces will make your graphic conform to slight contours and textures without any hassle.

Unique Features:

- ▶ Enhanced Dimensional Stability
- ▶ Easy to Convert, Print, and Apply, Optimizing your Workflow
- ▶ Low Shrink Adhesive System
- ▶ Strong Adhesion for Demanding Applications

Applications:

- ▶ Textured / Rough Surfaces
- ▶ Low Surface Energy Substrates
- Outdoor Walls

Performance & Physical Data	
Finish:	Satin
Durability (Unprinted):	7 Years
Roll Widths:	30" (0,76 m), 49" (1,24 m) 54" (1,37 m), 60" (1,52 m)
Roll Lengths:	50 Yards (45,72 m)
Adhesive:	High Tack, Permanent (Clear)
Release Liner:	Lay-Flat Polycoated
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlaminate:	Series 3210 Series 3220 Series 3420 ProTec Series 3960





200 Boysenberry Lane, Placentia, CA 92870, USA

EUROPE: a North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands



800 232 7161 / 714 985 6300

+31 0 70 354 4311

800 329 2756

January 2019