



ARLON

DPF V9500 VITAL.

Transform textured surfaces with DPF V9500, engineered for exceptional conformability for a paint-like finish. It's high-tack adhesive securely adheres to rough surfaces without lifting, shrinking, or popping over time. Designed for effortless installation, DPF V9500 is easily repositionable and has a wide application temperature range for hot and cold installations. Keep your graphics looking new with an extended durability of up to 10 years. Plus, its non-PVC, Polyurethane formula makes it the ideal sustainable solution. Elevate any wall with DPF V9500 — built for performance, made for impact.

Unique Features:

- ▶ Unmatched conformability to highly textured surfaces
- ▶ Optimal initial tack and long-term permanent adhesive for wall application
- ▶ 68% reduction in VOCs during manufacturing compared with PVC cast film
- ▶ Fire Certified to ASTM E84, EN 13501 and AS 5637

Applications:

- ▶ Building Wraps
- ▶ Wall Graphics (Interior, Exterior)

Performance & Physical Data

Finish:	Gloss
Durability (Unprinted):	10 Years
Roll Widths:	54" (1,37 m)
Roll Lengths:	50 Yards (45,72 m)
Adhesive:	Permanent, Repositionable (Tinted)
Release Liner:	Lay-Flat Polycoated with Low Profile Air-egress
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlamine:	Series V3370



Certified for
HP Latex Inks

USA

- a 200 Boysenberry Lane, Placentia, CA 92870
- p 800 232 7161 / +1 714 985 6300
- f +1 714 985 6305

EUROPE

- a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p +31 70 354 4311
- f +31 70 355 7721

CHINA

- a No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p +86 0536 6226568

arlon.com

June 2025