



ARLON

SLIP RESISTENT OVERLAMINATES

SERIES 3220 GLOSS & SERIES 3420 GLOSS

Series 3220 Gloss and Series 3420 Gloss are now approved under the UL 410 regulation for slip-resistance as an interior floor graphic material *. Pair it with Arlon DPF 4600GLX/MLX, DPF 8200 High Tack, or DPF 510GTR/MTR to protect your interior floor graphics. UL is an organization which has been testing and approving products for consumer safety for over a century, performing safety testing on electrical, mechanical and chemical products. To learn more about UL, visit: UL.com.

Unique Features:

- ▶ UL 410 approved for slip-resistance on floors
- ▶ Go-to overlaminate with multiple uses

Recommended Surfaces:

- ▶ Smooth Floors
- ▶ Low-Profile Carpet ◆

Performance & Physical Data

Finish:	Gloss
Roll Widths:	30" (0,76m) ✦, 48" (1,22m) 54" (1,37m), 60" (1,52m)
Roll Lengths:	25 Yards (22,86m) ▲ 50 Yards (45,72m)
Adhesive:	Permanent (Clear)
Release Liner:	Clay Coated
Compatible Films:	DPF 4600GLX / MLX DPF 8200 High Tack ◆ DPF 510GTR/MTR

* Arlon has not reformulated either product to meet this UL specification. Any product manufactured after August 30, 2019 is not officially approved by UL standard, however, it still possesses slip-resistant properties because there has not been any change in the construction of the product.

✦ 30" (0,76m) width available for Series 3220 only

▲ 25 Yards (22,86m) is only available for Series 3220 in 48" (1,22m) and 54" (1,37m) widths

◆ For interior floor graphics on carpet, Arlon recommends DPF 8200 High Tack only

