

Print Media Total System Warranty

Arlon warrants that Arlon brand films and media will perform and provide "outdoor durability" or "indoor durability" (1) for the period stated in the corresponding Technical Bulletin from the date of application under normal vertical exposure (2) conditions provided that the film is properly stored and is applied within one year of the original shipment date from Arlon. This warranty is contingent on material being processed using OEM recommended inks, premask and associated processing materials in accordance with recommended written processing instructions and being applied to properly prepared surfaces; cleaned and maintained in accordance with recommended application procedures.

Outdoor durability and indoor durability for the purpose of this warranty are defined as no appreciable deterioration in the product when seen from its intended viewing distance. Premature failure due to cracking, crazing, blistering or loss of adhesion shall constitute a breach of warranty if it occurs during the warranty period. Excessive color fading, chalking, edge lifting, tenting around rivets, gloss reduction or reflectivity shall also constitute a breach of warranty if it occurs during the warranty period. Replacement graphics will be warranted for the period corresponding to the remaining warranty period of the original failed graphics.

Exclusions: Graphics adhered to non-vertical areas of the vehicle (such as the hood, trunk or roof top) are excluded from Arlon's Print Media Total System Warranty. Film failure caused by ink over-saturation are not covered. Ink contamination and/or failures recognized by the respective OEM ink manufacturers will not be covered by this warranty.

PRODUCT COMPATIBILITY PROGRAMS

The durability for each warranted product compatibility program is found in the below chart.

Note: If the stated durability of an approved allied component (ink, toner, overlaminate) differs from that of the Arlon material, the finished graphics will be warranted for a period equal to the stated durability of the least durable component.

PREMIUM 7-YEAR OUTDOOR DURABILITY RATING			
QUALIFYING MEDIA:	SLX™ Cast Wrap	Premium White Cast Film with Repositionable Adhesive	
QUALIFYING OVERLAMINATE:	SERIES 3270 / SERIES 3220 / SERIES 3210 SERIES 3310	Cast Overlaminate	
QUALIFYING MEDIA:	DPF 6100XLP / DPF 6000XRP DPF 6000RP WHITE / DPF 6000RP CLEAR	Premium White/Clear Cast Film with Repositionable Adhesive	
QUALIFYING OVERLAMINATE:	SERIES 3220 / SERIES 3210 / SERIES 3270 SERIES 3200 / SERIES 3310	Cast Overlaminate	
QUALIFYING MEDIA:	DPF 6500	Premium White Translucent Cast Film with Permanent Adhesive	
QUALIFYING OVERLAMINATE:	SERIES 3220 / SERIES 3210 SERIES 3200 / SERIES 3350 / SERIES 3310	Cast or Anti-Graffiti Overlaminate	
QUALIFYING MEDIA:	DPF 6700 (See PIB for warranty exclusions)	Premium White Cast Film with Permanent Adhesive	
QUALIFYING OVERLAMINATE:	SERIES 3220 / SERIES 3210 / SERIES 3200 SERIES 3310	Cast Overlaminate	
QUALIFYING MEDIA:	DPF 9000	White Industrial Grade Calendered Film with Permanent Adhesive (Solvent Resistant)	
QUALIFYING OVERLAMINATE:	SERIES 3220 / SERIES 3420 / SERIES 3310	Cast or Calendered Overlaminate	

_				
	PREMIUM 7-YEAR OUTDOOR DUR			
QUALIFYING MEDIA:	DPF 5200	Printable Cast Etched Glass Film		
QUALIFYING MEDIA:	DPF 8000™ Ultra Tack / DPF 8200 High Tack DPF 8200X High Tack (See PIB for warranty exclusions)	White Premium Grade Calendered Film with Permanent Adhesive (Ultra Tack / High Tack)		
QUALIFYING OVERLAMINATE:	SERIES 3420 / SERIES 3220 / SERIES 3960 SERIES 3210 / SERIES 3310	Cast or Calendered Overlaminate		
QUALIFYING MEDIA:	DPF 4000	White Industrial Grade Calendered Film with Permanent Adhesive		
QUALIFYING OVERLAMINATE:	SERIES 3220 / SERIES 3420	Cast or Calendered Overlaminate		
QUALIFYING MEDIA:	IllumiNITE Wrap™ / DPF 2400XLP/ DPF 2400	Printable White Reflective Film with Permanent Adhesive		
QUALIFYING OVERLAMINATE:	SERIES 3220/ SERIES 3210/ SERIES 3200	Cast Overlaminate		
QUALIFYING MEDIA:	Fusion Wrap / CalWrap / DPF 4600GLX/MLX (See PIBs for warranty exclusions)	High Performance Calendered Film, Clean Removing Repositionable		
QUALIFYING OVERLAMINATE:	SERIES 3170 / SERIES 3210 / SERIES 3220 SERIES 3310 / SERIES 3420*↑ SERIES 3410*↑▲	Cast or Calendered Overlaminate (CalWrap & DPF 4600LX can also be used without overlaminate)		
INTERMEDIATE 5-YEAR OUTDOOR DURABILITY RATING				
QUALIFYING MEDIA:	DPF 4500G WHITE / DPF 4500G Clear DPF 4500GLX / DPF 4500MLX / DPF 4500GX DPF 4500GT / DPF 4500MT DPF 4550G WHITE ◆ DPF 4550GTX / DPF 4550MTX ◆ DPF 4550GT / DPF 4550MT ◆ Optima GLX / Optima GT ◆	Intermediate White Calendered Film with Permanent Adhesive		
QUALIFYING OVERLAMINATE:	SERIES 3420 / SERIES 3450 ▲ / SERIES 3170 SERIES 3220 / SERIES 3200	Cast or Calendered Overlaminate		
	SPECIALTY 4-YEAR OUTDO	OR DURABILITY RATING		
QUALIFYING MEDIA:	DPF 4300	Intermediate White Calendered Multi-Purpose Film with Removable Adhesive		
QUALIFYING OVERLAMINATE:	SERIES 3220 / SERIES 3410 * ▲	Cast or Calendered Overlaminate		
	PROMOTIONAL 3-YEAR OUTD	OOR DURABILITY RATING		
QUALIFYING MEDIA:	DPF 510G / DPF 510M DPF 510GT / DPF 510MT DPF 510GTR / DPF 510MTR DPF 510G-HT / DPF 510M-HT DPF 510GT-HT / DPF 510MT-HT DPF 510G-UT / DPF 510M-UT ▲ DPF 510GT-UT / DPF 510MT-UT ▲ DPF 510GTX / MTX	Promotional Digital Film		
QUALIFYING OVERLAMINATE:	SERIES 3510	Calendered Overlaminate		
	PROMOTIONAL 1-YEAR OUTD	OOR DURABILITY RATING		
QUALIFYING MEDIA:	DPF 45WF	One-Way Vision Window Film 60/40 Perforated Film		
QUALIFYING MEDIA:	DPF 47WF	One-Way Vision Window Film 70/30 Perforated Film		
QUALIFYING MEDIA:	DPF 410G / GT	Value Promotional Digital Film		
QUALIFYING MEDIA:	DPF 208	Eco-Polypropylene Roll-Up Banner		
QUALIFYING MEDIA:	DPF 210/ DPF 210PB	Polyester Roll-Up Xtreme Banner		
QUALIFYING MEDIA:	DPF 215	Polyester Pop-Up Banner		
	/	/		

		/		
PR	OMOTIONAL 1-YEAR OUTDOOR D	URABILITY RATING (CONTINUED)		
QUALIFYING MEDIA:	DPF 308 / DPF 308LH	8-oz. Mesh Scrim Banner		
QUALIFYING MEDIA:	DPF 310	10-oz. Frontlit Scrim Banner		
QUALIFYING MEDIA:	DPF 310BB	9-oz. Black Back Scrim Banner		
QUALIFYING MEDIA:	DPF 313 - 500D	13-oz. Frontlit Scrim Banner		
QUALIFYING MEDIA:	DPF 318	18-oz. Blockout Scrim Banner		
QUALIFYING MEDIA:	DPF 350	15-oz. Backlit Scrim Banner		
QUALIFYING MEDIA:	DPF 355	15-oz. Backlit Scrim Banner - 3 Year Outdoor Durability		
QUALIFYING MEDIA:	DPF 380	18-oz. Backlit Scrim Banner		
QUALIFYING MEDIA:	DPF 385	18-oz. Backlit Scrim Banner - 3 Year Outdoor Durability		
7-YEAR INDOOR DURABILITY RATING				
QUALIFYING MEDIA:	DPF 4200 MATTE/CANVAS	Interior Matte/Canvas Wall Decoration Film with Permanent Adhesive		
1-YEAR INDOOR DURABILITY RATING				
QUALIFYING MEDIA:	DPF 206	Interior Woven Wall Decoration Film with Removable Adhesive		
QUALIFYING MEDIA:	DPF 207	Interior Matte Wall Decoration Film with Removable Adhesive		
PREMIUM 15-YEAR INDOOR / 7-YEAR OUTDOOR DURABILITY RATING				
QUALIFYING MEDIA:	Ever Etched Cast	Premium Printable Cast Etched Glass Film with Repositionable Adhesive		
7-YEAR INDOOR / 5-YEAR OUTDOOR DURABILITY RATING				
QUALIFYING MEDIA:	Ever Etched Cal	Printable Calendered Etched Glass Film with Repositionable Adhesive		
t Use on flat and simple curves only 7 year warranty applies when paired with an Arlon cast overlaminate				

^{❖ 7} year warranty applies when paired with an Arlon cast overlaminate

In the event a breach of warranty occurs as defined above, Arlon's sole liability is outlined below:

I. GENERAL STATEMENT

DEFINITIONS

Outdoor durability for the extremely severe areas reduced warranty is provided. Refer to the Zone map for locations and corresponding durability ratings. Clean Removability is defined as removable with the assistance of heat or chemicals using Arlon recommended removal procedures. Clean removable products are guaranteed to leave no more than 25% adhesive residue during removal. Removal of graphics must occur within the warranty period listed above.

A. WARRANTY REMEDY

The exclusive remedy under Arlon's Print Media Total System Warranty shall be at Arlon's option the replacement or credit for the defective warranted products only. For failures during the second half of the graphics warranted life, Arlon material purchase price reimbursement will be calculated using the following formula:

REIMBURSEMENT FORMULA =

Arlon material purchase price X (warranty in months - number of months since application)

(warranty in months)

[▲] Available in EMEA

[◆] Available in EMEA & ANZ

B. LIMITATION OF WARRANTY

NOTIFICATION OF CLAIM

This warranty requires that Arlon be notified in writing of any claims within fourteen days of material failure. Claim notifications must include name and lot numbers for films and processing components, report of processing conditions and in-process test results, finished decal retain samples, installation date and location, name of installer and any other pertinent information requested. Arlon reserves the right to inspect all reported claims. Failure to comply constitutes a waiver of all rights under this warranty. This warranty applies to Arlon specified graphics programs only. Contact your Sales Representative for further details.

APPLICATION TO GLASS

Arlon accepts no liability for glass breakage. Glass may break under the stresses/caused by temperature changes across the surface, which could be amplified by the application of vinyl film.

MISUSE AND FORCE

Arlon has no obligations under this warranty with respect to products that have been modified or damaged through misuse, abuse, accident, neglect or mishandling by purchaser or purchaser's customer. For example, unless specifically claimed in a Technical Bulletin, graphics are not warranted against premature failure caused by chemical or mechanical means such as, but not limited to vandalism, cleaning solutions, paints, solvents, improperly used high pressure washing equipment, mechanical washing equipment, engine fuel spills, engine exhaust, steam, organic solvents or other spilled chemicals. Graphics applied to unsound surfaces or surfaces that subsequently crack, peel, outgas or become damaged beneath the graphic are not warranted for performance. Damage from fire, structural failure, lightening and other such events are not covered.

UNINTENDED USE OF PRODUCTS

Arlon products covered by this warranty are intended only for use by professional users and only for the intended uses as described in the corresponding Arlon Technical Bulletin. Before using for any other application, user shall determine the suitability of the product for its intended use and user assumes all risk and liability in connection therewith. To determine the best product for application Arlon always recommends testing prior to using the above products on the actual surface, especially for wall and floor application as product performance can vary greatly depending on the substrate, elemental exposure and surface preparation. In no event shall Arlon be liable for any incidental or consequential damages including, but not limited to, loss of profit, loss of use or production or loss of capital.

Arlon's liability on any claim of any kind shall in no case exceed the amount expressly provided for in this warranty. This limitation applies regardless of whether the damages are sought based on breach of warranty, breach of contract, negligence, strict liability in tort or any other legal theory.

- (1) Outdoor durability for the extremely severe areas will be two years or 50% less than the durability published in the appropriate technical bulletin: Southern Florida, AZ, NV, NM, UT, TX, Southern California, Mexico or other similar latitudes (please reference Zone Map below).
- (2) Vertical exposure is defined as \pm 10° from vertical. Applications greater than 10° from vertical and greater than 5° from the horizontal will be warranted at 50% the durability published in the appropriate technical bulletin. Horizontal applications are not warranted. Non-vertical applications occurring in extreme environments would be calculated at warranty limitations of (1) + (2).
- (3) This warranty is not extended to stainless steel surfaces or marine applications.
- (4) Specified films may be used for floor graphic applications but this warranty is not extended for the performance or clean removability of floor graphics materials.
- (5) If the stated durability of an approved allied component (ink, toner, clear coat) differs from that of the Arlon material the finished graphics will be warranted for a period equal to the stated durability of the least durable component.

ZONE MAP ZONE 1 ZONE 2

AUSTRIA BELARUS

BELGIUM CANADA CZECH REPUBLIC DENMARK ESTONIA FINLAND

GERMANY **GREENLAND** HUNGARY ICELAND IRELAND

LATVIA LIECHTENSTEIN LITUANIA LUXEMBOURG MOLDOVA

NORTHERN ASIAN COUNTRIES NORWAY

POLAND RUSSIA ROMANIA SCANDINAVIA SWEDEN SWITZERLAND UNITED STATES** UKRAINE UNITED KINGDOM THE NETHERLANDS

* Except for areas listed in ZONE 3

** Except for areas listed in ZONE 2 and ZONE 3

AUSTRALIA* AI BANIA BOLIVIA* BRAZIL **BOSNIA & HERZEGOVINA** BULGARIA CARIBBEAN ISLES

CENTRAL AMERICA CHILE*

CHINA COLOMBIA* CROATIA CYPRUS FRANCE GREECE HAWAII ITALY JAPAN KOREA MACEDONIA

MALTA MEDITERRANEAN ISLANDS

MEXICO* MONTENEGRO

NEW ZEALAND PARAGUAY PERU* PORTUGAL PUERTO RICO

SOUTH AFRICAN COAST SOUTHERN ASIAN COUNTRIES

SERBIA SLOVENIA SPAIN TURKEY

UNITED STATES
(South FL, AZ, NV, NM, TX, South CA, UT Desert Regions)

VENEZUELA*

VIRGIN ISLANDS

ARABIAN GULF REGION ARGENTINA

AUSTRALIA (Western Australia, Northern Territory & Queensland) INDIA

MIDDLE EAST

NORTH AFRICA - INCLUDING SAHARA NORTH CHILE NORTH COLUMBIA

NORTH VENEZUELA SOUTH & CENTRAL AFRICA SOUTH PERU

SOUTHERN MEXICO SOUTHWEST BOLIVIA

ELEVATIONS ABOVE ALTITUDES OF 1500 M (5000 FT)

November 2019

North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands

800 232 7161/+1 714 985 6300

+31 70 355 7721